Delivery-related technical data	
Pallet type-	pallet 2350x800mm
Package weight	400-500kg depending on the choice of package and accessories
Package dimensions (L x W x H)	260 x 255 x 130 cm
Product technical data	
Size	5 people 1bed/4seats
External dimensions (L x W x H)	245 x 245 x 100 cm
Internal dimensions (L x W x H)	195 x195x82 cm
External heater size (L x W x H)	-
Chimney height from the ground	**260cm** Chimney length 2 meters + 19 cm cap and chimney raised 41 cm from the ground in an integrated furnace
Chimney flue diameter	**129 mm**
Minimum base size	300 x 300 cm
Recommended base size	345 x 310 cm
Liner	
Material	Acrylic
Colors	Black Marble, White Marble
Thickness	pure acrylic sheet 5mm
Consolidation	hardening: molded acrylic is secured with three layers of fiberglass
Insulation	closed-cell polyurethane foam
Exterior Cladding	
WPC (Wood-plastic composite)	Black, Brown, Ivory
Spruce and Thermowood (the color of painted thermo wood is different from spruce)	RC 545 teak, RC 260 pinie/larchel, RC 555 kastanie, RC 720 palisander, RC 970 silbergrau, RC 660 Nussbaum, RC 790 ebenholz, 2265 grafito pilka, FT 20928 anthrazitgrau, RAL 7016 anthrazit
Water supply	
Capacity	**1500L at the waterline**
Water drain valve diameter	24 mm
Hydromassage system	
Model	DXD-315E (1,1kW) DXD -320E (1,5kW)
Number of stainless steel jets, all options	6/8/12/14/16/18/24
Power	6/8/12jets: 1,1 kW, 5 amp 14jets: 1,5 kW, 16/18/24 jets: 2,2 kW, 10 amp (two pumps 1.1kW)
Voltage	220 – 240 V AC 50 Hz

Air-jet system	
Model	DXD-6P
Number of stainless steel jets, all options	12/18/24
Power	12/18 jets, 750 W / 3.3 amp 24 jets, 1500 W, 6.6 amp (two pumps)
Voltage	220-240 V AC 50Hz/60Hz
Wind speed	55 km/h
Noise	70 dB
LED lighting	
Voltage	Input: 220 V AC Output: 12 V AC
Colour modes	red, deep blue, green, light purple, light blue, yellow, white, RGB
Number of LEDs, all options	1/2 LED liht underwater lights 7/11/15 LED stars underwater lights LED strip RGB
Water filtration	
Model	top mounted sand/fiber ball filter
Voltage	220 – 240 V AC 50 Hz
Power	0.14 kW / 0,6 amp
Capacity/flow:	86 l/min
Tank diameter	252mm
Tank height	389 mm
Fiber media replacement	Mountfield Aquawool Polysphere Filter Balls 450g 58475 or any equivalent
Enclosure Box for the water filtration unit (L x W x H)	580x600x700 mm
Skimmer	
Type	installed
Material	plastic
Max. temperature	40℃
Basket capacity	L
Combined	with UV-C lamp
Power	350W / 2 amp
Voltage	220-240V AC 50Hz
Flow:	167 l/min
UV-C	
Model	Blue Lagoon SpAOP UV-C 21W
Power	21 W / 0.2 amp
Voltage	230 V AC 50 / 60 Hz
Lamp life	9.000 h
Content (L)	10.000
Rec. Flow for 30mJ/m2	50 l/min (98%)
Max. flow	217 l/min
Max. pressure	1 bar
Min. temperature	1℃
Max. temperature	40℃

Heater type and fuel	
Wood fired stove	
Main heater material	Food grade stainless steel AISI 304 or AISI 316
Heating time	1−2 hours in summer, 2−3 hours in winter
Heater rated heating output	25kW
Electrical heater	
Model	Phalen Aqua compact
Power	3kW
Tension	230 V 1-phase (3-6 kW), 230 V 3-phase (3-18 kW), 400 V 3-phase (3-18 kW)
Min. flow	90 l/min
Max. flow	300 l/min
Max. pressure	2.5 bar (2.5 Pa)
Max. temperature	45℃
Rated power	220-240 V / 380-415 V 50-60 Hz
power consumption	**230 V, 1-phase** 3kW / 13amp 6kW / 26 amp
	230 V, 3-phase 3kW / 8amp 6kW / 15amp 9kW / 23amp
	400 V, 3-phase 3kW / 5amp 6kW / 9amp 9kW / 18amp
circulation pump for electric heater	
Model	DXD-310T-350
Power	350W / 2 amp
Voltage	220-240V AC 50Hz
Max. temperature	40℃
Capacity/flow:	167 l/min